

The Superior Air - Jacketed Hot Rubber Melters
(Propane, Diesel, & Electric Heat Systems Available)

From the Innovators of Rubber Master Technology

Asphalt Crack Sealers

All of our Air-Jacketed Melters are now available with the crack seal option. These units are the most compact, quickest and lightweight Asphalt Crack Sealers on the market. Available on or off the trailer for tight spots with a 20 Heated hose on a 360 degree swing boom with the option to go longer if needed. Call today for pricing on the most affordable crack sealers available. We can custom build to suit your needs.



A-210 Cracksealer shown

- 110 Volt Heated hose
- Available with Heated or non heated wand
- Agitator & Pump can be powered by Diesel, Gas or Electric motors
- Heat sources available: Diesel, Propane or Electric Elements
- Automatic temperature controls standard
- A-110 Model Available with or without trailer
- Heavy duty stainless steel fire tubes



The Superior Air - Jacketed Hot Rubber Melters
(Propane, Diesel, & Electric Heat Systems Available)

From the Innovators of Rubber Master Technology



A-500 Cracksealer shown

Specifications

Heat Transfer Oil	None Required.....	Fire tube.....	SCH 80 Stainless Steel
Capacity (Custom Sizes Available)	100, 200, 380, 500 US Gallons		
Agitator.....	Honda gas engine, 110 V Electric, or Diesel		
Overall Dimensions (Melter only)	varies		
Burner.....	Adjustable Liquid Propane or Optional Beckett Diesel Burners		
Temperature Controls..	Optional on Propane heated units, Standard on Diesel heated units		
Inner Shell	Rolled Steel		
Outer Shell	1/8" Rolled Steel		
Insulated Jacket	2" High Temp. Fiberglass		
Shipping Weight (Melter only)	varies		
Optional Trailer (w/Melter mounted)	varies		
Suspension Drop Axle and springs			
Tires	varies		
Trailer Chassis ..	4" Steel Channel on A-110 & A-210, 6" Steel Channel on A-380 & A-500		
Brakes	Electric		
Tow Hitch	As ordered c/w safety chain		
Pump	Viking Material Pump		
Heated Hose System	110V with a 20' Heated hose, Heated wand optional		